

DATASHEET - 250A 690V AC TYPE T FUSE



Fuse-link, high speed, 250 A, AC 690 V, 200 kA, BS88, 41 x 113 mm, aR, BS



Part no. **250A 690V AC TYPE T FUSE**
Catalog No. **250FM**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	250
Rated voltage			AC 690 V
Construction size			BS88
Size			41 x 113 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			BS
Shape			offset bolted tags
Standards/Regulations			BS88-4 IEC 60269-4
Optional accessories			fuse-holder BH-1133

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			
Rated voltage AC		V	690
Rated voltage DC		V	
Rated current		A	250
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	200
Colour code			
Type of fuse status indicator			None
Power loss at rated current		W	48
Mounting holes			
Centre-to-centre distance of connections		mm	